



REQUEST FOR QUOTATION (RFQ) No. 290-2023

Procurement Unit

The Tarlac State University (TSU), through its Bids and Awards Committee (BAC) and Procurement Unit, will undertake an **Alternative Method of Procurement through Negotiated Procurement** for the items stated below, in accordance with **Section 53.9 Small Value Procurement** of the Revised Implementing Rules and Regulations of Republic Act. No. 9184.

The TSU hereinafter referred to as "the Buyer", now requests submission of a price quotation for the subject below:

Purchase Request No.	DESCRIPTION/PARTICULARS	APPROVED BUDGET FOR THE CONTRACT (ABC) inclusive of VAT
2023-05-173 (PROC)	VARIOUS AUDIO AND VISUAL SUPPLIES	910,426.00
Purpose: Audio and Visual Supplies - APP 1st Quarter 2023		

Philgeps Posting: Active Date: 5/12/23 Closing Date: 5/18/23 Category: Audio & Visual Equipment Reference No.: 0742605

Interested suppliers are required to submit the following documents:

- Valid and Current Mayor's / Business Permit
- Latest Income / Business Tax Return
- Proof of PhilGeps Registration
- Omnibus Sworn Statement
- Brochure, if applicable

TSU Condition of Sale:

- Delivery Schedule: 40 calendar days from receipt of approved PO/NTP
- Bid Validity: 20 calendar days from submission of bids
- Delivery Site: Supply and Property Management Unit, Tarlac State University
(045) 606-8159 / (045) 982-2605
- Warranty shall be for a period minimum of three (3) months of expendable supplies, or a supplies/equipment after acceptance by the procuring entity of the delivered

Award of contract shall be made to the bidder with the lowest quotation for the subject goods which comply with the minimum technical specifications and other terms and conditions stated herein.

Any alteration, erasures, or overwriting shall be valid only if they are signed or initialed by the bidder or his/her duly authorized representative.

Submission of duly signed Price Quotation Form (Attachment 1) and eligibility documents is not later than 5/18/23 at the Procurement Unit, Admin Building Tarlac State University, Tarlac City. Open submission may be done manually or through email at tsucanvassing@gmail.com

The penalty for late deliveries is one tenth (1/10) of one (1) percent of the cost of the underperformed portion for every day of delay. Once the cumulative amount of liquidated damages reaches ten (10%) percent of the contract price, the procuring entity shall rescind the contract without prejudice to other courses of action and remedies open to it.

The TSU reserves the right to reject any and all bids, declare a failure of bidding, or not award the contract in accordance with Section 41 of R.A 9184 and its IRR, without thereby incurring any liability to the affected bidder or bidders.


ELENA MAY T. TEOFILO
 Head, Procurement Unit

PRICE QUOTATION

Date: 5/10/2023
 RFQ No. 290-2023
 PR No. 2023-05-173 (PROC)

The Bids and Awards Committee
 c/o Procurement Unit
 TSU, Tarlac City
 (045) 982 -4630 / (045) 606 -8157

Sir / Madam:

After having carefully read and accepted the terms and conditions in the Request for Quotation, hereunder is our price quotation for the item/s identified below:

ITEM NO.	UNIT	ITEM & DESCRIPTION	QUANTITY	UNIT PRICE	TOTAL PRICE
1	unit	LAPTEL , Lapel Microphone LAV -100 Single Portable Lavalier UHF Wireless Microphone w/ 20 Selectable Frequencies, UHF Frequencies 683.1 to 695.1 MHz, 20 Selectable frequencies, Freq. Resp.: 50Hz-15KHz, Transmitter & receiver Battery Type: Rechargeable Li-Battery 3.7 V(400mA), Can also connect with mobile phone	20		
2	unit	LED LIGHT , CCT 5600K CRI 95+ TLCI 95+ CQS 92 SSI (D56) 74 Output Wattage 200W Power Consumption 250W Operating Current 5.2A Operating Voltage, Battery 48V/5.5A Operating Voltage, Power Supply Output 48V Operating Voltage, Power Supply Input AC 100~240V 50/60HZ Operating Temperature -20°C~45°C Control Methods On-board, Sidus Link (Sidus Mesh™) Wireless Operating Range (Bluetooth) ≤ 80m Screen Type LCD Firmware Upgradeable Sidus Link OTA Cooling Method Active Cooling Power Supply Head Cable 3-pin X Max Head Cable Length 3m AC Power Cable Locking IEC AC Power Cable (1.5m) Accessory Mount Bowens Mount Umbrella Holder Yes Mounting 16mm 5/8in (Baby Pin) Weight, Lamp Head 1577g / 3.477lbs Weight, Power Supply 813g / 1.792lbs Weight, Total w/ Box 3960g / 8.73lbs Dimensions, Lamp Head w/o Mounting Column 207*115*115mm / 8.15*4.528*4.528in Dimensions, Lamp Head w/ Mounting Column 207*154*212mm / 8.15*6.063*8.346in Dimensions, Lamp Head w/ Mounting Column & Reflector 313*185*247mm / 12.323*7.283*9.724in Dimensions, Power Supply 170*84*30mm / 6.693*3.307*1.181in Dimensions, Carrying Box Carrying Box	2		

Warranty : _____

The above-quoted price is inclusive of all costs and applicable taxes

Very truly yours,

AUTHORIZED REPRESENTATIVE:

Signature : _____
 Printed Name : _____
 Date : _____
 Company Name Registered : _____
 E-mail Address : _____
 Contact no. : _____

BANK DETAILS:

Bank Name : _____
 Bank Address : _____
 Bank Account Name : _____
 Bank Account Number : _____

PRICE QUOTATION

Date: 5/10/2023
 RFQ No. 290-2023
 PR No. 2023-05-173 (PROC)

The Bids and Awards Committee
 c/o Procurement Unit
 TSU, Tarlac City
 (045) 982 -4630 / (045) 606 -8157

Sir / Madam:

After having carefully read and accepted the terms and conditions in the Request for Quotation, hereunder is our price quotation for the item/s identified below:

ITEM NO.	UNIT	ITEM & DESCRIPTION	QUANTITY	UNIT PRICE	TOTAL PRICE
3	unit	LIGHT DOME, SE 33.5" (85cm) Key Features 1.5- and 2.5-Stop Front Diffusers 1.5-Stop Removable Interior Diffuser 45° Fabric Grid Soft, Wraparound Quality of Light TOP FEATURES - 33.5" (85cm) Parabolic Softbox. - 1.5 & 2.5 Stop Diffusion Cloths. - Fabric Light Control Grid. - Collapses Flat for Easy Travel. - Bowens Accessory Mount. - Perfect for Content Creators. Compatibility Compatible with the Bowens Mount LED lights, such as the Amaran 100d, 100x, 200d, and 200x, as well as the Aputure LS 600d Pro, 300d II, 300x, and 120d II. It will also work with lights from other manufacturers who use this popular mount.	2		
4	unit	MEGAPHONE, Handheld, 15W, Rated Power Output 15W, Battery Life for voice use 14h, Colour Grey, Weight 1.1kg, Depth 346mm, Height 291 mm, Width 210 mm	3		
5	piece	MICROPHONE CABLES, Connector 1 3-Pin XLR Male Connector 2 3-Pin XLR Female Cable Length 20' / 6.1 m Shielding 95% Spiral Wire Gauge 24 AWG Contact Plating Silver"	4		

Warranty : _____

The above-quoted price is inclusive of all costs and applicable taxes

Very truly yours,

AUTHORIZED REPRESENTATIVE:

Signature : _____
 Printed Name : _____
 Date : _____
 Company Name Registered : _____
 E-mail Address : _____
 Contact no. : _____
BANK DETAILS:
 Bank Name : _____
 Bank Address : _____
 Bank Account Name : _____
 Bank Account Number : _____

PRICE QUOTATION

Date: 5/10/2023
 RFQ No. 290-2023
 PR No. 2023-05-173 (PROC)

The Bids and Awards Committee
 c/o Procurement Unit
 TSU, Tarlac City
 (045) 982 -4630 / (045) 606 -8157

Sir / Madam:

After having carefully read and accepted the terms and conditions in the Request for Quotation, hereunder is our price quotation for the item/s identified below:

ITEM NO.	UNIT	ITEM & DESCRIPTION	QUANTITY	UNIT PRICE	TOTAL PRICE
6	piece	MICROPHONE , wireless, sensitivity 12dBuV (80db S/N), sensitivity range 12-32	6		
7	piece	MIXER AMPLIFIER , Power Rating 220 Watts @ 4 Ohms 130 Watts @ 8 Ohms (UA) 130 Watts @ 8 Ohms (H) Total Harmonic Distortion (THD) Less than 0.5 % (THD+N) +14 dB @ 20 Hz, 1 kHz, 20 kHz, GAIN control: all nominal Power Supply 120 V 60 Hz, 450 W Dimensions 17.40 x 10.78 x 11.26"" (442 x 274 x 286mm) Weight 22 lbs. (10 kg)"	1		
8	unit	MOBILE STABILIZER , Handle Dimensions 2.4x1.9x6.4 inch (61.8x48.2x161.5 mm) Weight (including battery) 201 g 501 g (including gimbal) Model OM150 Gimbal Name Zenmuse M1 Model ZM01 Dimensions 4.92x4.29x3.57 inch (Folded) 125.06x109.15x90.98 mm Weight 300 g Consumption 2.5 W Angular Vibration Range ±0.03° Controllable Range Pan : ±150° Roll : ±25° Tilt : -125° to +35° Mechanical Range Pan : ±165° Roll : -50° to +90° Tilt : -140° to +50° Max Controllable Speed 120°/s Mobile Phone Width Range 2.31-3.34 inch (58.6-84.8 mm) Intelligent Battery Model HB01-522365 Type LiPo Capacity 980 mAh Energy 10.8 Wh Voltage 11.1 V Charging Temperature 5° to 40° C (41° to 104° F) Operating Temperature 0° to 40° C (32° to 104° F) Wireless Model Bluetooth Low Energy 4.0	5		

Warranty : _____

The above-quoted price is inclusive of all costs and applicable taxes
 Very truly yours,

AUTHORIZED REPRESENTATIVE:

Signature : _____
 Printed Name : _____
 Date : _____
 Company Name Registered : _____
 E-mail Address : _____
 Contact no. : _____
BANK DETAILS:
 Bank Name : _____
 Bank Address : _____
 Bank Account Name : _____
 Bank Account Number : _____

PRICE QUOTATION

Date: 5/10/2023
 RFQ No. 290-2023
 PR No. 2023-05-173 (PROC)

The Bids and Awards Committee
 c/o Procurement Unit
 TSU, Tarlac City
 (045) 982 -4630 / (045) 606 -8157

Sir / Madam:

After having carefully read and accepted the terms and conditions in the Request for Quotation, hereunder is our price quotation for the item/s identified below:

ITEM NO.	UNIT	ITEM & DESCRIPTION	QUANTITY	UNIT PRICE	TOTAL PRICE
9	unit	MULTICOLOR MINI LED LIGHT , Product Highlights 95% BT 2020 Gamut Coverage Full HSI Color Control 0 to 100% Dimming OLED Display with Control Wheel Accessories Mount 1/4"-20 Female, Magnetic Lighting Color Temperature 3200 to 6500K Dimmable Yes, 0 to 100% Lens Number of LED 12 General Dimension 3.7 x 2.4 x 0.7" / 93 x 61 x 17 mm Warranty 1 Year Power/Battery Capacity: 2600 mAh Lithium-Ion Polymer (LiPo) Input connector: USB Type-C	3		
10	lot	RECORDING STUDIO ACCESSORIES , 5 Panel Foldable Studio Microphone Isolation Shield Recording Sound Absorber Foam Panel pop filter	1		
11	unit	SOUND SYSTEM , 15" 2 Way 400W Powered Portable Sound System Plastic Cabinet AC220V or DC12V (With built-in Rechargeable Batteries) With 2 Wireless Microphone With 2 Mic Input (1 XLR, 1 PL55) With FM Radio, Bluetooth, Guitar Input (Shared with Mic 2 input), USB & SD Port With 5 Band Equalizer and LCD Display With Aux / Line In and Line Out With Remote Control, Handle and WheelsVV	1		

Warranty : _____

The above-quoted price is inclusive of all costs and applicable taxes
 Very truly yours,

AUTHORIZED REPRESENTATIVE:

Signature : _____
 Printed Name : _____
 Date : _____
 Company Name Registered : _____
 E-mail Address : _____
 Contact no. : _____

BANK DETAILS:

Bank Name : _____
 Bank Address : _____
 Bank Account Name : _____
 Bank Account Number : _____

PRICE QUOTATION

Date: 5/10/2023
 RFQ No. 290-2023
 PR No. 2023-05-173 (PROC)

The Bids and Awards Committee

c/o Procurement Unit

TSU, Tarlac City
 (045) 982 -4630 / (045) 606 -8157

Sir / Madam:

After having carefully read and accepted the terms and conditions in the Request for Quotation, hereunder is our price quotation for the item/s identified below:

ITEM NO.	UNIT	ITEM & DESCRIPTION	QUANTITY	UNIT PRICE	TOTAL PRICE
12	piece	SPEAKER TRIPOD STAND , Material of Construction Aluminum, Height Adjustment Range Per Stand: 3.8 to 7.5' / 1.1 to 2.3 m, Mount Size 1.375" / 34.9 mm 1.5" / 38.1 mm Load Capacity Per Stand: 120 lb / 54.4 kg Weight Per Stand: 6.1 lb / 2.8 kg"	4		
13	unit	SPEAKER, Portable and Wireless Bluetooth Speaker , dimension 15.70" x 17.20", weight 27.80, transducers 2x 216 mm(8") woofer, 2 x 70mm (2.75") tweeter, output power 800W RMS (IEC60268), power output 100-240 VAC~50/60Hz, frequency response 35Hz-20kHz (-6db)	6		
14	piece	SPEAKER, POWERED SPEAKERS Power rating (W, Continuous) 500, Power rating (W, Peak) 1000, Frequency Response Hz (±3 dB) 50 - 20,000, Maximum SPL (peak dB) 127, Coverage Pattern (Nominal) 90° x 60°, Weight (lbs) 39.0, Height (in) 27.8, Depth (in) 14.4, Width (in) 17.3, Height (mm) 707.0, Width (mm) 439.0, Depth (mm) 365.0, Weight (kg) 17.7	4		
15	unit	WIRELESS MICROPHONE SYSTEM , Dual-channel stereo receiver for cameras and mobile devices Portable charging case for the transmitter and receiver Vivid OLED display on both transmitter and receiver Selectable Mono/Stereo output mode Real time headphone monitor	4		

Warranty : _____

The above-quoted price is inclusive of all costs and applicable taxes
 Very truly yours,

AUTHORIZED REPRESENTATIVE:

Signature : _____
 Printed Name : _____
 Date : _____
 Company Name Registered : _____
 E-mail Address : _____
 Contact no. : _____

BANK DETAILS:

Bank Name : _____
 Bank Address : _____
 Bank Account Name : _____
 Bank Account Number : _____

PRICE QUOTATION

Date: 5/10/2023
 RFQ No. 290-2023
 PR No. 2023-05-173 (PROC)

The Bids and Awards Committee
 c/o Procurement Unit
 TSU, Tarlac City
 (045) 982 -4630 / (045) 606 -8157

Sir / Madam:

After having carefully read and accepted the terms and conditions in the Request for Quotation, hereunder is our price quotation for the item/s identified below:

ITEM NO.	UNIT	ITEM & DESCRIPTION	QUANTITY	UNIT PRICE	TOTAL PRICE
		Mic input and Line input 8 hours battery life on one single charge One button easy pairing Display Transmitter 1 x OLED (Audio Level, Battery Status, Mute, Power, Signal Strength) Receiver 1 x OLED (Battery Status, Data Transmission, Mute, Power, Recharging, Sync, Transmitter Battery Status) Form Factor Microphone: Lavalier Maximum SPL 110 dB SPL Polar Pattern Omnidirectional. Sound Field Mono. Range Operating Range: 328' / 100 m (Line of Sight). Input/Output Receiver Audio 1 x 1/8" / 3.5 mm TRS Female Unbalanced Mic Output 1 x 1/8" / 3.5 mm TRS Female Unbalanced Headphone Output Transmitter Audio 1 x 1/8" / 3.5 mm TRS Female Unbalanced Input. General Cable Microphone: Length 4.1' / 1.2 m			
16	piece	Wired MICROPHONES Neodymium capsule design Supercardioid pattern Principle: Dynamic moving coil motor Frequency Response : 80 – 18kHz Sensitivity : -53 dBV (2.3mV) @ 1Pa Impedance : 500 ohms Max SPL >148dB Note: with microphone box (box of three)	3		
17	piece	Quad Connectors 3 External Line Return (XLR) F connectors 3 XLR M connectors	1		

Warranty : _____

The above-quoted price is inclusive of all costs and applicable taxes
 Very truly yours,

AUTHORIZED REPRESENTATIVE:

Signature : _____
 Printed Name : _____
 Date : _____
 Company Name Registered : _____
 E-mail Address : _____
 Contact no. : _____

BANK DETAILS:

Bank Name : _____
 Bank Address : _____
 Bank Account Name : _____
 Bank Account Number : _____

PRICE QUOTATION

Date: 5/10/2023
 RFQ No. 290-2023
 PR No. 2023-05-173 (PROC)

The Bids and Awards Committee
 c/o Procurement Unit
 TSU, Tarlac City
 (045) 982 -4630 / (045) 606 -8157

Sir / Madam:

After having carefully read and accepted the terms and conditions in the Request for Quotation, hereunder is our price quotation for the item/s identified below:

ITEM NO.	UNIT	ITEM & DESCRIPTION	QUANTITY	UNIT PRICE	TOTAL PRICE
		3 mic wires stereo 10M (each) Note: Connector Type: XLR, Cable Type: XLR, Compatible Devices: Speaker, microphone, Color: Black, Gauge: 21.0-24.0, Item Weight: about 10.4 ounces, Product Dimensions: 11.1 x 8.6 x 1.2 inches, Size: 10 Feet			
18	unit	3.5MM JACK TO RCA CABLE , "Color : Black Material: PVC Connector A: 3.5 mm Male Connector B: 2RCA Male Connection Split/Duplication: 1 : 2 Cable Length: 1.17M /46" Outside Diameter of 3.5mm Plug : approx 1/8 inch Type: Audio 3.5 mm 1/8 inch to 2 RCA Conversion Cable" Warranty: 6 months warranty	3		
19	set	4 CHANNELS MINI STEREO HEADPHONE AMPLIFIER , Features: Ultra-compact stereo headphone amplifier for studio and stage application. With 4 headphone output channels and 1 input channel. Volume of each output channel can be controlled independently. Provides highest audio quality for each headphone even at maximum volume. Ultra low noise operational amplifier for outstanding audio performance. Compact 4-channel stereo headphone amplifier can be used for up to four headphones at the same time for simultaneous listening of main mix with separate volume control. Comes with a DC 12V power adapter.	1		

Warranty : _____

The above-quoted price is inclusive of all costs and applicable taxes
 Very truly yours,

AUTHORIZED REPRESENTATIVE:

Signature : _____
 Printed Name : _____
 Date : _____
 Company Name Registered : _____
 E-mail Address : _____
 Contact no. : _____

BANK DETAILS:

Bank Name : _____
 Bank Address : _____
 Bank Account Name : _____
 Bank Account Number : _____

PRICE QUOTATION

Date: 5/10/2023
 RFQ No. 290-2023
 PR No. 2023-05-173 (PROC)

The Bids and Awards Committee
 c/o Procurement Unit
 TSU, Tarlac City
 (045) 982 -4630 / (045) 606 -8157

Sir / Madam:

After having carefully read and accepted the terms and conditions in the Request for Quotation, hereunder is our price quotation for the item/s identified below:

ITEM NO.	UNIT	ITEM & DESCRIPTION	QUANTITY	UNIT PRICE	TOTAL PRICE
20	unit	AUDIO JACK 3.5MM , "Name: 3. 5mm AUX Audio Cable AWG: 29AWG Appearance Color: Black Interface Type: 3.5mm Male to Male Interface Process: Gold plated Jacket Material: PVC+Fabric Braided Shell Material: Aluminum alloy Outer Diameter: 3.0mm Cable Length: 3m Transmission Conductor: Enamelled copper Product Warranty: One year"	2		
21	set	DIGITAL VIDEO SWITCHER REMOTE CONTROLLER , Communication Interface : RS-232 Baud Rate : 38400 ODD Update : USB Power Supply : Input AC 100 ~ 240V Switching Adaptor Output DC 12V Power Consumption : 5W Operating Temperatur Power : DC 12V, 0.5A Accessory : RS-232 Transmission Cable, Power Adapter, Thank You Card What's in the Box 1 x Video Switcher product 1 x AD Switch DC 12V 1 x DB9P TO DB9P Cable Warranty: at least 1 year warranty	1		
22	set	DUAL WIRELESS MIC TRANSMITTER AND RECEIVER , RF Modulation: GFSK (Gauss Frequency Shift Keying) Frequency band: 2.4G (2405-2478MHz) Frequency response: 35Hz- 14KHz±3dB Signal/Noise: 84dB or more Distortion: 0.05% or less (32ohm, 1 KHz, 65 mW output) FR output level: 3mW Earphone output level: 32ohm, 65mW Reception sensitivity: -90dB+/- 3dB / OdB=1V/Pa, 1KHz Audio input connector: 3.5mm mini jack Operation range: 50m (164 ft)(without obstacle) Power requirement: 2 * AAA battery(not included) Consumption power: Transmitter: 3V/70mA Receiver: 3V/70mA Warranty : at least 1 year warranty	2		

Warranty : _____

The above-quoted price is inclusive of all costs and applicable taxes
 Very truly yours,

AUTHORIZED REPRESENTATIVE:

Signature : _____
 Printed Name : _____
 Date : _____
 Company Name Registered : _____
 E-mail Address : _____
 Contact no. : _____
BANK DETAILS:
 Bank Name : _____
 Bank Address : _____
 Bank Account Name : _____
 Bank Account Number : _____

PRICE QUOTATION

Date: 5/10/2023
 RFQ No. 290-2023
 PR No. 2023-05-173 (PROC)

The Bids and Awards Committee
 c/o Procurement Unit
 TSU, Tarlac City
 (045) 982 -4630 / (045) 606 -8157

Sir / Madam:

After having carefully read and accepted the terms and conditions in the Request for Quotation, hereunder is our price quotation for the item/s identified below:

ITEM NO.	UNIT	ITEM & DESCRIPTION	QUANTITY	UNIT PRICE	TOTAL PRICE
23	unit	HD / SD CHARACTER GENERATOR KIT , Video Input HDMI x 1 HD-SDI x 1 Video Output : HD-SDI x 2 Input Format : 1080i 50/59/60 720p 50/59/60 576i 50 480i 59 Contro : I By Dip Switch/PC F/W : Upgrade Ethernet (RJ-45) Power : DC 12V What's in the Box 1x character generator kit 1x AD Switch DC 12 ,Warranty : at least 1 year warranty	1		
24	unit	HD-SDI CABLE (20 METERS) , Canare 3CFB Low Loss Cable with Canare BNC Connectors Length : 20 Meters, Warranty: 1 year warranty	1		
25	unit	HEADPHONE W/ MIC , Speaker Impedance : 32 Ohms Sensitivity : 94 dB SPL + 4 dB Sensitivity : -17 dBV/Pa +/- 4 dB Frequency response (Headset) : 20 Hz - 20 kHz Frequency response (Microphone) : 100 Hz -10 kHz Cable length : 2.33m Connections : USB-A compatible, Remote call control: Call answer/ignore/end/hold, redial, mute, volume +/- Warranty : atleast 2-year warranty	23		
26	set	POWERED 5-INCH TWO-WAY POWERED STUDIO MONITOR , Features: Patented Image Control Next-generation transducers Dual Class-D power amps New Boundary EQ3-position HF Trim switch Specifications : Lf Driver Size: 203mm (5") Hf Driver Size: 25mm (1") Hf Driver Type: Soft Dome Crossover: 1725hz 4th Order Acoustic Linkwitz-Riley Ok For Use Near Magnetically Sensitive Equipment: Yes Input Sensitivity (-10dbv Input): 92db / 1m Power Configuration: Bi-Amplified Hf Driver Power Amp: 41w,	2		

Warranty : _____

The above-quoted price is inclusive of all costs and applicable taxes
 Very truly yours,

AUTHORIZED REPRESENTATIVE:

Signature : _____
 Printed Name : _____
 Date : _____
 Company Name Registered : _____
 E-mail Address : _____
 Contact no. : _____
BANK DETAILS:
 Bank Name : _____
 Bank Address : _____
 Bank Account Name : _____
 Bank Account Number : _____

PRICE QUOTATION

Date: 5/10/2023
 RFQ No. 290-2023
 PR No. 2023-05-173 (PROC)

The Bids and Awards Committee
 c/o Procurement Unit
 TSU, Tarlac City
 (045) 982 -4630 / (045) 606 -8157

Sir / Madam:

After having carefully read and accepted the terms and conditions in the Request for Quotation, hereunder is our price quotation for the item/s identified below:

ITEM NO.	UNIT	ITEM & DESCRIPTION	QUANTITY	UNIT PRICE	TOTAL PRICE
		Class-D Lf Driver Power Amp: 41w, Class-D Frequency Response ($\pm 3\text{db}$): 49hz – 20khz Frequency Range (-10db): 43hz – 24khz Low Frequency Extension (-10db): 43hz Maximum Continuous Spl*: 94db Maximum Peak Spl***: 108db Maximum Peak Input Level (-10dbv / +4dbu): +6dbv / +20.3dbu System Distortion Criteria: <10% Thd At Maximum Output With Full Compressor / Limiter Engagement Electrical Distortion Criteria: 0.2% Thd @ 1khz / 2.83vrms Output; <1% Thd @ 1khz, Full Rated Output Signal To Noise Ratio: 75dba (A-Weighted), 70dbr (Unweighted), Relative To 2.83vrms Output Coverage Horizontal X Vertical: 120° X 90° Analog Input Types: 1 X Xlr Female, 1 X Trs Female, Balanced Hf Trim Control: -2db, 0db, +2db Boundary Eq: Lf Shelf @ 50hz: -3db, -1.5db, 0db Ac Input Voltage: 100 – 240vac ($\pm 10\%$), 50 / 60hz Enclosure Type: Ported Enclosure Construction: 15mm Mdf ,Enclosure Finish: Matte.Black Pvc Baffle Construction: Injection-Molded Structural Abs Cabinet Dimensions (H X W X D***): 298 X 185 X 231mm (11.7" X 7.3" X 9.1") Warranty : at least 1 year warranty			
27	unit	SDI CABLE , "Name: SDI Male To Male Video Converter Cable Color: Black Length: 10M OD: 5.0MM Wire Core: Pure Copper Resolution: 1920*1080P Compatible With Multiple Devices: Broadcast level SDI digital signal transmission: HDMI To SDI Converter/SDI Distributor/Profession VCR/Network HHD VCR/SDI To HDMI Converter/SDI Capture Card/Surveillance Cameras"	15		

Warranty : _____

The above-quoted price is inclusive of all costs and applicable taxes
 Very truly yours,

AUTHORIZED REPRESENTATIVE:

Signature : _____
 Printed Name : _____
 Date : _____
 Company Name Registered : _____
E-mail Address : _____
 Contact no. : _____
BANK DETAILS:
 Bank Name : _____
 Bank Address : _____
 Bank Account Name : _____
 Bank Account Number : _____

PRICE QUOTATION

Date: 5/10/2023
 RFQ No. 290-2023
 PR No. 2023-05-173 (PROC)

The Bids and Awards Committee
 c/o Procurement Unit
 TSU, Tarlac City
 (045) 982 -4630 / (045) 606 -8157

Sir / Madam:

After having carefully read and accepted the terms and conditions in the Request for Quotation, hereunder is our price quotation for the item/s identified below:

ITEM NO.	UNIT	ITEM & DESCRIPTION	QUANTITY	UNIT PRICE	TOTAL PRICE
28	unit	SDI TO HDMI 3G ADAPTER , 1x SD/HD/3G-SDI Input & 1 x Loop Output, 1 x HDMI Type A Output DCI 2K SDI In/Out 1080p60 HDMI Out ,3D LUT for Calibrating or Loop Output SDI A/B Selection USB Power Embedded Audio Compact, Rugged Design LED Video & Power Signal Indicators Features HDMI & SDI Outputs One SD/HD/3G-SDI input One HDMI output and one SD/HD/3G-SDI loop output Compact, Rugged Design Robust metal housing and rugged connectors USB Type-C port for powering via a compatible component like a monitor or laptop Updatable via the USB Type-C port and your Mac or PC 3D LUT Support Supports a 7-point 3D LUT for color calibrating your monitor, television, or projector Outputs LUT for monitoring via SDI loop output Wider Resolution Support SDI support up to DCI 2Kp60 HDMI support up to 1080p60 Embedded Audio Supports embedded HDMI input and embedded SDI output LED Indicators LED indicators for video and power signals Versatile Power Options Power from a monitor, laptop, or other component using the USB Type-C port Separately available 100-240 AC power supply with four socket adapters Includes 100 to 240V AC power supply with international socket adapters ,Warranty : at least 1 year warranty	1		
29	unit	STREAMING USB MICROPHONE , Specifications: High-and-low-end heavy tone Shins in voice-over, stream, podcast USB setup, all-metal construction Latency-free headphone monitoring .Quick mute button with LED indicator Headphone & microphone controls Type : Condenser Polar Pattern : Cardioid Frequency Response : 40-20kHz Sensitivity : -45d±3dB S/N Ratio : 85dB, Bit Rate & Sample Rate: 16 bit 48kHz Power Supply : 5V/80mA USB power Output Connection : USB 2.0 Warranty : atleast 1 year warranty	7		

Warranty : _____

The above-quoted price is inclusive of all costs and applicable taxes
 Very truly yours,

AUTHORIZED REPRESENTATIVE:

Signature : _____
 Printed Name : _____
 Date : _____
 Company Name Registered : _____
 E-mail Address : _____
 Contact no. : _____
BANK DETAILS:
 Bank Name : _____
 Bank Address : _____
 Bank Account Name : _____
 Bank Account Number : _____



Bid Notice Abstract

Request for Quotation (RFQ)

Reference Number 9742605
Procuring Entity TARLAC STATE UNIVERSITY
Title Various Audio and Visual Supplies
Area of Delivery Tarlac

Solicitation Number: 290-2023	Status	Pending
Trade Agreement: Implementing Rules and Regulations		
Procurement Mode: Negotiated Procurement - Small Value Procurement (Sec. 53.9)	Associated Components	3
Classification: Goods	Bid Supplements	0
Category: Audio and Visual Equipment	Document Request List	0
Approved Budget for the Contract: PHP 910,426.00		
Delivery Period: 40 Day/s	Date Published	12/05/2023
Client Agency:	Last Updated / Time	11/05/2023 09:10 AM
	Closing Date / Time	18/05/2023 13:00 PM
Contact Person: Tutchie Panlilio Clerk TSU, Romulo Blvd. San Vicente, Tarlac City, Philippines Tarlac City Tarlac Philippines 2300 63-2-092058494963 elenamayteofilo73@gmail.com		

Description

for University use

Line Items

Item No.	Product/Service Name	Description	Quantity	UOM	Budget (PHP)
1	LAPEL	Lapel Microphone LAV -100 Single Portable Lavalier UHF Wireless Microphone w/ 20 Selectable Frequencies, UHF Frequencies 683.1 to 695.1 MHz, 20 Selectable frequencies, Freq. Resp.: 50Hz-15KHz, Transmitter & receiver Battery Type: Rechargeable Li-Batte	20	Unit	50,000.00
2	LED LIGHT	CCT 5600K CRI 95+ TLCI 95+ CQS 92 SSI (D56) 74 Output Wattage 200W Power Consumption 250W Operating Current 5.2A Operating Voltage, Battery 48V/5.5A Operating Voltage, Power Supply Output 48V Operating Voltage, Power Sup	2	Unit	40,000.00
3	LIGHT DOME	SE 33.5" (85cm) Key Features 1.5- and 2.5-Stop Front Diffusers 1.5-Stop Removable Interior Diffuser 45° Fabric Grid Soft, Wraparound Quality of Light TOP FEATURES - 33.5" (85cm) Parabolic Softbox. - 1.5 & 2.5 Stop Diffusion Cloths. - Fabric Light	2	Unit	20,000.00
4	MEGAPHONE	Handheld, 15W, Rated Power Output 15W, Battery Life for voice use 14h, Colour Grey, Weight 1.1kg, Depth 346mm, Height 291 mm, Width 210 mm	3	Unit	9,000.00
5	MICROPHONE CABLES	Connector 1 3-Pin XLR Male Connector 2 3-Pin XLR Female Cable Length 20' / 6.1	4	Piece	6,076.00

		m Shielding 95% Spiral Wire Gauge 24 AWG Contact Plating Silver"			
6	MICROPHONE	wireless, sensitivity 12dBuV (80db S/N), sensitivity range 12-32	6	Piece	4,200.00
7	MIXER AMPLIFIER	Power Rating 220 Watts @ 4 Ohms 130 Watts @ 8 Ohms (UA) 130 Watts @ 8 Ohms (H) Total Harmonic Distortion (THD) Less than 0.5 % (THD+N) +14 dB @ 20 Hz, 1 kHz, 20 kHz, GAIN control: all nominal Power Supply 120 V 60 Hz, 450 W Dimensions 17.40 x 10.78 x	1	Piece	38,000.00
8	MOBILE STABILIZER	Handle Dimensions 2.4x1.9x6.4 inch (61.8x48.2x161.5 mm) Weight (including battery) 201 g 501 g (including gimbal) Model OM150 Gimbal Name Zenmuse M1 Model ZM01 Dimensions 4.92x4.29x3.57 inch (Folded) 125.06x109.15x90.98 mm Weight	5	Unit	50,000.00
9	MULTICOLOR MINI LED LIGHT	Product Highlights 95% BT 2020 Gamut Coverage Full HSI Color Control 0 to 100% Dimming OLED Display with Control Wheel Accessories Mount 1/4"-20 Female, Magnetic Lighting Color Temperature 3200 to 6500K Dimmable Yes, 0 to 100% Lens Number of	3	Unit	30,000.00
10	RECORDING STUDIO ACCESSORIES	5 Panel Foldable Studio Microphone Isolation Shield Recording Sound Absorber Foam Panel pop filter	1	Lot	5,000.00
11	SOUND SYSTEM	15" 2 Way 400W Powered Portable Sound System Plastic Cabinet AC220V or DC12V (With built-in Rechargeable Batteries) With 2 Wireless Microphone With 2 Mic Input (1 XLR, 1 PL55) With FM Radio, Bluetooth, Guitar Input (Shared with Mic 2 input), USB & SD	1	Unit	13,000.00
12	SPEAKER TRIPOD STAND	Material of Construction Aluminum, Height Adjustment Range Per Stand: 3.8 to 7.5' / 1.1 to 2.3 m, Mount Size 1.375" / 34.9 mm 1.5" / 38.1 mm Load Capacity Per Stand: 120 lb / 54.4 kg Weight Per Stand: 6.1 lb / 2.8 kg"	4	Piece	5,600.00
13	SPEAKER, Portable and Wireless Bluetooth Speaker	dimension 15.70" x 17.20 ", weight 27.80, transducers 2x 216 mm(8") woofer, 2 x 70mm (2.75") tweeter, output power 800W RMS (IEC60268), power output 100-240 VAC~50/60Hz, frequency response 35Hz-20kHz (-6db)	6	Unit	239,400.00
14	SPEAKER, POWERED SPEAKERS	Power rating (W, Continuous) 500, Power rating (W, Peak) 1000, Frequency Response Hz (±3 dB) 50 - 20,000, Maximum SPL (peak dB) 127, Coverage Pattern (Nominal) 90° x 60°, Weight (lbs) 39.0, Height (in) 27.8, Depth (in) 14.4, Width (in) 17.3, Height (mm)	4	Piece	36,900.00
15	WIRELESS MICROPHONE SYSTEM,	Dual-channel stereo receiver for cameras and mobile devices Portable charging case for the transmitter and receiver Vivid OLED display on both transmitter and receiver Selectable Mono/Stereo output mode Real time headphone monitor	4	Unit	80,000.00
16	Wired MICROPHONES	Neodymium capsule design Supercardioid pattern Principle: Dynamic moving coil motor Frequency Response : 80 - 18kHz Sensitivity : -53 dBV (2.3mV) @ 1Pa Impedance : 500 ohms Max SPL >148dB Note: with microphone box (box of three)	3	Piece	13,500.00
17	Quad Connectors	3 External Line Return (XLR) F connectors 3 XLR M connectors 3 mic wires stereo 10M (each) Note: Connector Type: XLR, Cable Type: XLR, Compatible Devices: Speaker, microphone, Color: Black, Gauge: 21.0-24.0, Item Weight: about 10.4 ounces, Product	1	Piece	1,200.00
18	3.5MM JACK TO RCA CABLE	Color : Black Material: PVC Connector A: 3.5 mm Male Connector B: 2RCA Male Connection Split/Duplication: 1 : 2	3	Unit	450.00

		Cable Length: 1.17M /46' Outside Diameter of 3.5mm Plug : approx 1/8 inch Type: Audio 3.5 mm 1/8 inch to 2 RCA Conversion Cable" Warranty			
19	4 CHANNELS MINI STEREO HEADPHONE AMPLIFIER,	Features: Ultra-compact stereo headphone amplifier for studio and stage application. With 4 headphone output channels and 1 input channel. Volume of each output channel can be controlled independently. Provides highest audio quality for each headph	1	Set	6,000.00
20	AUDIO JACK 3.5MM	Name: 3. 5mm AUX Audio Cable AWG: 29AWG Appearance Color: Black Interface Type: 3.5mm Male to Male Interface Process: Gold plated Jacket Material: PVC+Fabric Braided Shell Material: Aluminum alloy Outer Diameter: 3.0mm Cable Length: 3m Transmission C	2	Unit	600.00
21	DIGITAL VIDEO SWITCHER REMOTE CONTROLLER	Communication Interface : RS-232 Baud Rate : 38400 ODD Update : USB Power Supply : Input AC 100 ~ 240V Switching Adaptor Output DC 12V Power Consumption : 5W Operating Temperatur Power : DC 12V, 0.5A Accessory : RS-232 Transmission Cable, Power Adap	1	Set	33,000.00
22	DUAL WIRELESS MIC TRANSMITTER AND RECEIVER	RF Modulation: GFSK (Gauss Frequency Shift Keying) Frequency band: 2.4G (2405-2478MHz) Frequency response: 35Hz-14KHz±3dB Signal/Noise: 84dB or more Distortion: 0.05% or less (32ohm, 1 KHz, 65 mW output) FR output level: 3mW Earphone output level: 32	2	Set	14,000.00
23	HD / SD CHARACTER GENERATOR KIT	Video Input HDMI x 1 HD-SDI x 1 Video Output : HD-SDI x 2 Input Format : 1080i 50/59/60 720p 50/59/60 576i 50 480i 59 Contro : I By Dip Switch/PC F/W : Upgrade Ethernet (RJ-45) Power : DC 12V What's in the Box 1x character generator kit 1x AD Swi	1	Unit	47,000.00
24	HD-SDI CABLE (20 METERS)	Canare 3CFB Low Loss Cable with Canare BNC Connectors Length : 20 Meters, Warranty: 1 year warranty	1	Unit	6,000.00
25	HEADPHONE W/ MIC	Speaker Impedance : 32 Ohms Sensitivity : 94 dB SPL + 4 dB Sensitivity : -17 dBV/Pa +/- 4 dB Frequency response (Headset) : 20 Hz - 20 kHz Frequency response (Microphone) : 100 Hz -10 kHz Cable length : 2.33m Connections : USB-A compatible, Remote ca	23	Unit	57,500.00
26	POWERED 5-INCH TWO-WAY POWERED STUDIO MONITOR	Features: Patented Image Control Next-generation transducers Dual Class-D power amps New Boundary EQ3-position HF Trim switch Specifications : Lf Driver Size: 203mm (5") Hf Driver Size: 25mm (1") Hf Driver Type: Soft Dome Crossover: 1725hz 4th Or	2	Set	56,000.00
27	SDI CABLE	"Name: SDI Male To Male Video Converter Cable Color: Black Length: 10M OD: 5.0MM Wire Core: Pure Copper Resolution: 1920*1080P Compatible With Multiple Devices: Broadcast level SDI digital signal transmission: HDMI To SDI Converter/SDI Distributor/Pr	15	Unit	15,000.00
28	SDI TO HDMI 3G ADAPTER	1x SD/HD/3G-SDI Input & 1 x Loop Output, 1 x HDMI Type A Output DCI 2K SDI In/Out 1080p60 HDMI Out ,3D LUT for Calibrating or Loop Output SDI A/B Selection USB Power Embedded Audio Compact, Rugged Design LED Video & Power Signal Indicators Featur	1	Unit	5,000.00
29	STREAMING USB MICROPHONE	Specifications: High-and-low-end heavy tone Shins in voice-over, stream, podcast USB setup, all-metal construction Latency-free headphone monitoring .Quick mute button with LED indicator Headphone & microphone controls Type : Condenser Polar Pattern	7	Unit	28,000.00

Other Information

The bidders must download the attached documents in the associated component section.

Created by Tutchie Panlilio

Date Created 11/05/2023

The PhilGEPS team is not responsible for any typographical errors or misinformation presented in the system. PhilGEPS only displays information provided for by its clients, and any queries regarding the postings should be directed to the contact person/s of the concerned party.

© 2004-2023 DBM Procurement Service. All rights reserved.

[Help](#) | [Contact Us](#) | [Sitemap](#)